



Heriot-Watt University  
Research Gateway

## Investigation of laser beam scanning strategies for 100 W nanosecond pulsed fibre laser engraving of metals

### Citation for published version:

Dondieu, S, Włodarczyk, KL, Harrison, P, Rosowski, A, Gabzdyl, J, Reuben, RL & Hand, DP 2019, 'Investigation of laser beam scanning strategies for 100 W nanosecond pulsed fibre laser engraving of metals', 38th International Congress on Applications of Lasers and Electro-Optics 2019, Orlando, United States, 7/10/19 - 10/10/19.

### Link:

[Link to publication record in Heriot-Watt Research Portal](#)

### Document Version:

Early version, also known as pre-print

### General rights

Copyright for the publications made accessible via Heriot-Watt Research Portal is retained by the author(s) and / or other copyright owners and it is a condition of accessing these publications that users recognise and abide by the legal requirements associated with these rights.

### Take down policy

Heriot-Watt University has made every reasonable effort to ensure that the content in Heriot-Watt Research Portal complies with UK legislation. If you believe that the public display of this file breaches copyright please contact [open.access@hw.ac.uk](mailto:open.access@hw.ac.uk) providing details, and we will remove access to the work immediately and investigate your claim.

## **Investigation of laser beam scanning strategies for 100 W nanosecond pulsed fibre laser engraving of metals.**

**S.D. Dondieu<sup>1</sup>, K.L. Wlodarczyk<sup>1</sup>, P. Harrison<sup>2</sup>, A. Rosowski<sup>2</sup>, J. Gabzdyl<sup>2</sup>,  
R.L. Reuben<sup>1</sup>, D.P. Hand<sup>1</sup>,**

*1- Institute of Photonics and Quantum Sciences, School of Engineering and Physical Sciences,  
Heriot-Watt University, Edinburgh EH14 4AS, UK*

*2- SPI Lasers UK Ltd, 6 Wellington Park Tollbar Way, Hedge End, Southampton, S030 2QU UK*

*Corresponding author: [sdd1@hw.ac.uk](mailto:sdd1@hw.ac.uk)*

Laser engraving using high average power nanosecond pulsed fibre lasers is an increasingly popular technique to generate high-quality permanent inscribed structures in the surface of a variety of materials, in particular metals. As with any manufacturing process, overall speed is always critical and new higher average power laser systems offer the attractive prospect of reducing process time and hence cost. As a multi-pass process, however, laser engraving is a complex combination of peak and average power and thermal accumulation in the material; hence the fundamental laser process parameters of pulse energy, scan speed etc must be re-optimised when translating the process to a higher average power laser system.

We demonstrate in this paper that scanning strategies and parametric selection can remediate the thermal issues associated with high average power nanosecond laser applications. In particular, building on our earlier work on laser machining of glass, we demonstrate that interlaced laser beam scanning can provide a better-optimised solution than conventional raster scanning approaches. We investigate the impact of scanning patterns on the material removal rate, surface roughness and morphology during laser engraving of aluminium, brass and stainless steel. Ultimately, we demonstrate that high-quality engraving is achievable with high average power (100W) nanosecond pulsed fibre lasers using optimised scanning strategies and optimised pulses through SPI's pulse tuning capability.